Application No.: 10/720,389 Page 3

Art Unit: 2833

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

 (Currently amended) An electrical connector, comprising:

a housing body having a tubular plugging face for plugging [[in]] to a mating connector, said tubular plugging face having a sectional shape of a substantially square with respect to a sectional plane perpendicular to a direction of plugging into said mating connector,

said tubular plugging face including a square tubular portion having a rectangular section in a plane perpendicular to said plugging direction and a cylindrical portion having a circular section in said plane sectional shapes of a square and a circle, respectively, with respect to said sectional plane, which are overlapped with each other,

said circular section having a diameter greater than a height of but smaller than a width of said rectangular section and overlapping a central portion of said rectangular section in said plane; and

at least one key or at least one key groove provided on or in said cylindrical portion [[and]] for preventing a plugging error to said mating connector.

2. (Currently amended) The electrical connector according to claim 1, wherein said tubular plugging face includes at least one additional key or at least one additional key or at least one additional key groove provided on or in said square tubular portion.

Application No.: 10/720,389 Page 4

Art Unit: 2833

3. (Currently amended) The electrical connector according to claim 1 or 2, wherein said electrical connector is a plug connector having a plugging projection section,

said tubular plugging face <u>is</u> provided [[in]] <u>on</u> an outer surface of said plugging projection section, and said key groove provided in an outer surface of said cylindrical portion.

4. (Currently amended) The electrical connector according to claim 1 or 2, wherein said electrical connector is a receptacle connector having a plugging cavity section,

said tubular plugging face <u>is</u> provided on an inner surface of said plugging cavity section, <u>and</u>
said key <u>is</u> provided [[in]] <u>on</u> an inner surface of said cylindrical portion.

- 5. (Original) The electrical connector according to claim 1 or 2, wherein said cylindrical portion accommodates a coaxial terminal which is concentric with said cylindrical portion.
- 6. (Original) The electrical connector according to claim 5, wherein said coaxial terminal comprises a cylindrical outer conductor and a projection extending in a plugging direction of said outer conductor, wherein a groove for receiving said projection is provided in a coaxial terminal of said mating connector.
- 7. (Currently amended) The electrical connector according to claim 3, wherein said receptacle plug connector comprises [[a]] at least one flexible lock arm provided outside a region of said cylindrical portion but inside a region of said square tubular portion, extending

Application No.: 10/720,389 Page 5

Art Unit: 2833

in said plugging direction, and having a lock engagement claw at a [[top]] \underline{front} end thereof.

8. (Original) The electrical connector according to claim 7, wherein said cylindrical portion accommodates a coaxial terminal which is concentric with said cylindrical portion and said square tubular portion accommodates a signal terminal between cylindrical portion and said flexible lock arm.